

Curve Graphite 520lm 3000K Ra>80 Trailing edge dimming

Article code: 623341
 EAN: 7021986233414



Electrical

System wattage: 7W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light technic

Type of light source: LED
 Luminous flux: 520lm
 Efficacy: 74 lm/W
 Colour temperature: 3000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L70/B10>50,000
 Light distribution: Direct
 Optic: Glass Clear
 Beam angle: 110°/110°

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: C
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Aluminium
 Colour: Graphite
 Optics: Tempered glass

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
 Connection: Screwless terminal block

Dimensions

Width (mm) W: 320
 Height (mm) H: 60
 Depth (D): 103
 Weight (kg) gross/net: 1.68 / 1.4

Packaging

Packing dimensions (mm): 330 x 120 x 70

