EcoLine Office

Max. luminaires per circuit breaker:

EcoLine Office 1200 White 4540lm 4000K Ra>80 On/Off

Article code: EAN:

Electrical System wattage:

Voltage:

8246090517 5703821172417

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



30W 220-240V B10: 19, B16: 30, C10: 31, C16: 51

Light technic Type of light source: Luminous flux: Efficacy: Colour temperature: Colour rendering (CRI): MacAdams factor: Lifetime: Light distribution: Optic: UGR:	LED 4540lm 151 lm/W 4000K Ra>80 SDCM: 3 L80/B10>50,000 Direct/Indirect 60/40% Double parabolic louvre, satin matt UGR<16
Control/Dimming Type:	On/Off
Protection Luminaire class: IP Class:	Class I IP20
Energy and approvals Contains light source of energy class: Breeam:	C Fulfils Hea 01 for flicker free lighting
Materials and finish Housing: Colour: Optics:	Sheet steel White (Pure white, 25% gloss) Aluminium
Mounting/Connection Mounting: Module: Wire set: Cable: Connection:	Suspended, Indoor 1200 2x2m wire kit w/loop M13 w/2 brackets Cable 3x0,75mm² 2,5m w/ Schuko white Screwless terminal block
Dimensions Length (mm) L: Width (mm) W:	1200 142

Width (mm) W:
Height (mm) H:

Packaging Packing dimensions (mm):

Weight (kg) gross/net:

1255 x 146 x 95

81

6.2/6









