

Econ LED



Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light.

Econ LED








Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
White				
 <p>181184 Econ LED White 740lm 3000K Ra>80 Wireless Actuator 10W LED 74 lm/W SDCM:3 L70/B50>45,000 Beam: 120°, Direct, Opal</p>	Class II IP44 IK10	Wireless Actuator	Surface, Indoor Screwless terminal block	Ø300 x H92
 <p>181193 Econ LED White 790lm 3000K Ra>80 Trailing edge 10W LED 79 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP44 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø300 x H92
 <p>181194 Econ LED White 790lm 3000K Ra>80 Sensor 10W LED 79 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP44 IK10	Sensor	Surface, Indoor Screwless terminal block	Ø300 x H92
 <p>181195 Econ LED White 790lm 3000K Ra>80 Sensor Wireless 10W LED 79 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP44 IK10	Sensor Wireless	Surface, Indoor Screwless terminal block	Ø300 x H92
Accessories				
 <p>1633 Econ LED Diffuser</p>				Ø245 x H70