



Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light.



Product- and environment images







Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
10W					
	111893 Econ White E27 500lm 2700K Ra>80 Trailing edge dimming 10W LED 50 lm/W SDCM:6 L70/B50>50,000 Beam: 120°, Direct, Opal	Class II IP21 ceiling / IP20 wall IK10	Trailing edge dimming	Surface, Indoor Screwless terminal block	Ø280 x H85
	111894 Econ White E27 500lm 2700K Ra>80 Sensor 10W LED 50 lm/W SDCM:6 L70/B50>50,000 Beam: 120°, Direct, Opal	Class II IP21 ceiling / IP20 wall IK10	Sensor	Surface, Indoor Screwless terminal block	Ø280 x H85
22W					
	111391 Econ White 2700K Ra>80 On/Off 22W Compact fluorescent lamp Beam: 120°, Direct, Opal	Class II IP21 ceiling / IP20 wall IK10	On/Off	Surface, Indoor Screwless terminal block	Ø280 x L280 x W280 x H85
Others					
	121195 Econ White 2xE27 with security screw Sensor Beam: 120°, Direct, Opal	Class I IP21 ceiling / IP20 wall IK10	Sensor	Surface, Indoor Screwless terminal block	Ø280 x H85
	141192 Econ Midi Alu White E27 Sensor Beam: 120°, Direct, Opal	Class I IP44 IK10	Sensor	Surface, Indoor Screwless terminal block	Ø350 x L350 x W350 x H98
	141193 Econ Midi Alu White 2xE27 Beam: 120°, Direct, Opal	Class I IP44 IK10		Surface, Indoor Screwless terminal block	Ø350 x H98
	141194 Econ Midi Alu White 2xE27 with security screw	Class I IP44 IK10		Surface, Indoor Screwless terminal block	Ø350 x H98
	Beam: 120°, Direct, Opal				

Article codes



Article Protection Control gear Mounting/Connection Dimensions

121194
Econ White 2xE27 with security screw

0280 x H85