

Etne White 730lm 3000K Ra>80 On/Off

Article code: 143090
 EAN: 7021981430900

**Electrical**

System wattage: 11W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 70, B16: 112, C10: 86, C16: 138

Light technic

Type of light source: LED
 Luminous flux: 730lm
 Efficacy: 66 lm/W
 Colour temperature: 3000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B10>50,000
 Minimum ambient temperature: -25°C
 Light distribution: Direct
 Optic: Opal
 Beam angle: 114°
 Visible flicker (PstLM): 0.47
 Stroboscopic flicker (SVM): 0.13
 Photobiological safety: RG 0

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class II
 IK Class: IK07
 IP Class: IP20

Energy and approvals

Contains light source of energy class: E
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: UV-stabilized polycarbonate
 Colour: White
 Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor
 Connection: Screwless terminal block

Dimensions

Height (mm) H: 50
 Diameter (mm) D: 220
 Weight (kg) gross/net: 0.44 / 0.331

Packaging

Packing dimensions (mm): 230 x 225 x 55

