Frame Square Maxi



Frame Square Maxi White 1980lm 3000K Ra>80 Emergency 3H

Article code: 605345

FAN: 7021986053456

= This article is produced by order, with an expected delivery time of 3-4 weeks.



LED

Electrical

System wattage: 21W Voltage: 220-240V Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: Luminous flux: 1980lm Emergency lumen: EM 360 lm Efficacy: 94 lm/W 3000K Colour temperature: Colour rendering (CRI): Ra>80 MacAdams factor: SDCM: 3 L70/B20>100,000 Lifetime: L80/B20>75.000 Lifetime: Minimum ambient temperature: 0°C Light distribution: Direct Optic: Opal 110° Beam angle: Photobiological safety: RG 0 ULOR (Yes, when ceiling mounted

Control/Dimming

Emergency 3H Type:

Protection

Class II Luminaire class: IK Class: IK10 IP Class: IP66 Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor Screwless terminal block Connection:

Dimensions

Length (mm) L: 310 Width (mm) W: 310 Height (mm) H: 77 Weight (kg) gross/net: 3.65 / 3.45

Packaging

Packing dimensions (mm): 318 x 318 x 92











