

SG Hovden Black Midi 1140lm 3000K Ra>80 Trailing edge dimming

Article code: 630085
EAN: 7021986300857



Electrical

System wattage: 12W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 47, B16: 67, C10: 47, C16: 67

Light technic

Type of light source: LED
Luminous flux: 1140lm
Efficacy: 95 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B10>100,000
Light distribution: Direct
Optic: Lens
Beam angle: 36°
Visible flicker (PstLM): 0
Stroboscopic flicker (SVM): 0.01
ULOR (Yes, up to 35° tilt angle

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I
IK Class: IK10
IP Class: IP67

Energy and approvals

Contains light source of energy class: F

Materials and finish

Housing: Aluminium
Colour: Black
Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Outdoor
Cable: Cable 2m
Connection: Includes cable and plug

Dimensions

Length (mm) L: 100
Width (mm) W: 61
Height (mm) H: 116
Weight (kg) gross/net: 0.969 / 0.881

Packaging

Packing dimensions (mm): 160 x 120 x 80

