

## Hurdal 600 White 1590lm 3000K Ra>80 On/Off

Article code: 113100  
 EAN: 7021981131005



### Electrical

System wattage: 12W  
 Voltage: 220-240V  
 Frequency (Hz): 50/60Hz  
 Max. luminaires per circuit breaker: B10: 40, B16: 60, C10: 40, C16: 60  
 Leakage current (mA): 0.21

### Light technic

Type of light source: LED  
 Light source included: Yes  
 Luminous flux: 1590lm  
 Efficacy: 133 lm/W  
 Colour temperature: 3000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L80/B20>100,000  
 Lifetime: L90>50,000  
 Light distribution: Direct  
 Optic: Opal  
 UGR: UGR<25  
 Visible flicker (PstLM): 0.14  
 Stroboscopic flicker (SVM): 0.02

### Control/Dimming

Type: On/Off

### Protection

Luminaire class: Class I

### Energy and approvals

Contains light source of energy class: C

### Materials and finish

Housing: Steel  
 Optics: UV-stabilized polycarbonate

### Mounting/Connection

Mounting: Surface, Indoor  
 Module: 600  
 Connection: Screwless terminal block

### Dimensions

Length (mm) L: 600  
 Width (mm) W: 73  
 Height (mm) H: 72  
 Weight (kg) gross/net: 1.1 / 0.95

### Packaging

Packing dimensions (mm): 608 x 83 x 83

