

Hurdal 1200 White 3460lm 3000K Ra>80 On/Off

Article code: 113101
 EAN: 7021981131012



Electrical

System wattage: 24W
 Voltage: 220-240V
 Frequency (Hz): 50/60Hz
 Leakage current (mA): 0.25

Light technic

Type of light source: LED
 Light source included: Yes
 Luminous flux: 3460lm
 Efficacy: 144 lm/W
 Colour temperature: 3000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B20>100,000
 Lifetime: L90>50,000
 Light distribution: Direct
 Optic: Opal
 UGR: UGR<25
 Visible flicker (PstLM): 0.09
 Stroboscopic flicker (SVM): 0.03

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: C

Materials and finish

Housing: Steel
 Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor
 Module: 1200
 Connection: Screwless terminal block

Dimensions

Length (mm) L: 1200
 Width (mm) W: 73
 Height (mm) H: 72
 Weight (kg) gross/net: 1.9 / 1.65

Packaging

Packing dimensions (mm): 1208 x 83 x 83

