

## Hurdal 1500 White 4640lm 3000K Ra>80 On/Off

Article code: 113102  
 EAN: 7021981131029



### Electrical

System wattage: 31W  
 Voltage: 220-240V  
 Frequency (Hz): 50/60Hz  
 Max. luminaires per circuit breaker: B10: 14, B16: 23  
 Leakage current (mA): 0.31

### Light technic

Type of light source: LED  
 Light source included: Yes  
 Luminous flux: 4640lm  
 Efficacy: 150 lm/W  
 Colour temperature: 3000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L80/B20>100,000  
 Lifetime: L90>50,000  
 Light distribution: Direct  
 Optic: Opal  
 UGR: UGR<25  
 Visible flicker (PstLM): 0.02  
 Stroboscopic flicker (SVM): 0.09

### Control/Dimming

Type: On/Off

### Protection

Luminaire class: Class I

### Energy and approvals

Contains light source of energy class: C

### Materials and finish

Housing: Steel  
 Optics: UV-stabilized polycarbonate

### Mounting/Connection

Mounting: Surface, Indoor  
 Module: 1500  
 Connection: Screwless terminal block

### Dimensions

Length (mm) L: 1500  
 Width (mm) W: 73  
 Height (mm) H: 72  
 Weight (kg) gross/net: 2.3 / 2

### Packaging

Packing dimensions (mm): 1508 x 83 x 83

