

Inspire R



Inspire R Black 300 950lm 3000K Ra 98 DALI-2 / Push Dim

Article code: 212430
EAN: 7021982124303



Electrical

System wattage: 15W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Luminous flux: 950lm
Efficacy: 63 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra 98
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Lens
Beam angle: 55°
UGR: UGR<19
Photobiological safety: RG 1

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class II SELV
IP Class: IP20

Energy and approvals

Contains light source of energy class: E
Breem: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)

Mounting/Connection



Mounting: Recessed, Indoor
Module: Recessed
Connection: Screwless terminal block

Dimensions

Length (mm) L: 303
Width (mm) W: 62
Height (mm) H: 40
Weight (kg) gross/net: 0.585 / 0.519

Packaging

Packing dimensions (mm): 317 x 121 x 54



7 0 2 1 9 8 2 1 2 4 3 0 3