

Junistar Lux Square White 2X 1240lm 4000K Ra 98 Trailing edge dimming

Article code: 902592
 EAN: 7021989025924



Electrical

Wattage: 2x7W
 System wattage: 17W
 Voltage: 220-240V
 Frequency (Hz): 50/60Hz
 Max. luminaires per circuit breaker: B10: 52, B16: 84, C10: 52, C16: 84

Light technic

Type of light source: LED
 Luminous flux: 1240lm
 Efficacy: 73 lm/W
 Colour temperature: 4000K
 Colour rendering (CRI): Ra 98
 MacAdams factor: SDCM: 1
 Lifetime: L90/B10>100,000
 Light distribution: Direct
 Optic: Reflector
 Beam angle: 42°
 UGR: UGR<22

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II SELV

Energy and approvals

Contains light source of energy class: F
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Aluminium
 Colour: White (RAL 9003)
 Optics: Tempered glass

Mounting/Connection

Mounting: Recessed, Indoor
 Connection: Screwless terminal block

Dimensions

Length (mm) L: 175
 Width (mm) W: 95
 Height (mm) H: 50
 Cut-out (mm): 83
 Ceiling void depth (mm): 48
 Weight (kg) gross/net: 0.74 / 0.617

Packaging

Packing dimensions (mm): 235 x 130 x 60

