Jupiter Pro Soft



Jupiter Pro Soft White 1850lm 4000K Ra>90 Trailing edge dimming

Article code: 940356

EAN: 7021989403562

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 22W

Voltage: 220-240V

Light technic

Type of light source: LED Luminous flux: 1850lm Efficacy: 84 lm/W Colour temperature: 4000K Colour rendering (CRI): Ra>90 SDCM: 2 MacAdams factor: Lifetime: L90/B10>100.000 Light distribution: Direct Optic: Reflector Beam angle: 35°

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II SELV IP Class: IP65/IP20

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium Colour: White (RAL 9003) Optics: Tempered glass

Mounting/Connection

Mounting: Recessed, Indoor / Outdoor Connection: Quick connector

Dimensions

 Height (mm) H:
 130

 Diameter (mm) D:
 114

 Cut-out (mm):
 83

 Distance to flammable materials:
 50mm

 Weight (kg) gross/net:
 0.635 / 0.54

Packaging

Packing dimensions (mm): 152 x 143 x 140







