

Lineal recessed Corner White 1970lm 4000K Ra>80 DALI / Push Dim

Article code: 8246095716
 EAN: 5703821180221



Electrical

System wattage: 17W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 15, B16: 24, C10: 24, C16: 38

Light technic

Type of light source: LED
 Luminous flux: 1970lm
 Efficacy: 116 lm/W
 Colour temperature: 4000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B10>100,000
 Lifetime: L93/>50,000
 Light distribution: Direct
 UGR: UGR<28
 Photobiological safety: RG 0

Control/Dimming

Type: DALI / Push Dim

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
 Colour: White (RAL 9003)

Mounting/Connection





Mounting: Recessed, Indoor
 Module: Corner
 Connection: 5-pole Winsta mini with 5x2,5mm² through wiring

Dimensions

Length (mm) L: 627
 Width (mm) W: 581
 Height (mm) H: 70
 Weight (kg) gross/net: 2.6 / 2.6

Packaging

Packing dimensions (mm): 652 x 604 x 81



cd/km η = 100 %

— C0/C180
 — C90/C270



5 7 0 3 8 2 1 1 8 0 2 2 1