Nano Tilt

Control/Dimming

Protection



Nano Tilt White In/out 240lm 2700K Ra>90 Driver 350mA ordered separately

Article code: 907016

EAN: 7021989070160

 (C€)
 (iii)
 (50°30°)
 (P65)
 (∀∀)
 (14)
 (14)

4W

4W

Electrical
Wattage:

System wattage:

Light technicType of light source:LEDLuminous flux:240lmEfficacy:60 lm/WColour temperature:2700KColour rendering (CRI):Ra>90MacAdams factor:SDCM: 2Lifetime:L70/B50>50,000

Light distribution: Direct
Optic: Reflector medium
Beam angle: 36°
UGR: UGR<22

Photobiological safety: RG 1

Type: Driver 350mA ordered separately

Luminaire class: Class III IP Class: IP65

Energy and approvals

Contains light source of energy class: G

Contains light source of energy class:

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: Glass

 Mounting/Connection

 Mounting:
 Recessed, Indoor / Outdoor

 Dimensions

 Height (mm) H:
 29

 Diameter (mm) D:
 48

 Cut-out (mm):
 40

 Weight (kg) gross/net:
 0.047 / 0.0415

PackagingPacking dimensions (mm):55 x 55 x 55









