

Prelude



Mirror luminaire made of aluminium with diffuser made of Acrylic (PMMA). Can be installed with either with concealed or visible cable.




Design: Hallvard Jakobsen

Product- and environment images







Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
Brushed steel				
 197345 Prelude Brushed steel 960lm 3000K Ra>90 Trailing edge dimming 16W LED 60 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge dimming	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
Brushed steel, w/ outlet				
 197341 Prelude Brushed steel w/ outlet 890lm 2700K Ra>90 Trailing edge dimming 14W LED 64 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge dimming	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
Chrome				
 198324 Prelude Chrome 2700K Ra>80 On/Off 14W Fluorescent lamp D=16 mm Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	On/Off	Surface, Indoor Screwless terminal block	W606 x H70 x D80
White				
 111324 Prelude White 2700K Ra>80 On/Off 14W Fluorescent lamp D=16 mm Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	On/Off	Surface, Indoor Screwless terminal block	W606 x H70 x D80
 111340 Prelude White 1020lm 2700K Ra>90 Trailing edge dimming 14W LED 73 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge dimming	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>111345 Prelude White 1060lm 3000K Ra>90 Trailing edge dimming 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal</p>	<p>Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>L510 x W70 x H80 x D80</p>
White, w/ 2 x outlet				
 <p>111343 Prelude White w/ 2 x outlet 1020lm 2700K Ra>90 Trailing edge dimming 14W LED 73 lm/W SDCM:3 L70/B10>50,000 Direct, Opal</p>	<p>Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>L630 x W70 x H81 x D81</p>
 <p>111344 Prelude White w/ 2 x outlet 1000lm 2700K Ra>90 Trailing edge dimming 16W LED 63 lm/W SDCM:3 L70/B10>50,000 Direct, Opal</p>	<p>Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>W630 x H70 x D80</p>
 <p>111349 Prelude White w/ 2 x outlet 1060lm 3000K Ra>90 Trailing edge dimming 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal</p>	<p>Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>W630 x H70 x D80</p>
White, w/ outlet				
 <p>111341 Prelude White w/ outlet 1020lm 2700K Ra>90 Trailing edge dimming 14W LED 73 lm/W SDCM:3 L70/B10>50,000 Direct, Opal</p>	<p>Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>L560 x W70 x H80 x D80</p>

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 111346 Prelude White w/ outlet 1060lm 3000K Ra>90 Trailing edge dimming 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge dimming	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
 111347 Prelude White w/ outlet 1060lm 3000K Ra>90 Trailing edge dimming 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge dimming	Surface, Indoor Screwless terminal block	W560 x H70 x D80