Rax 150 U19

Max. luminaires per circuit breaker:

Rax 150 U19 White 2210lm 3000K Ra>80 Trailing edge dimming

Article code: EAN:

Electrical System wattage:

Voltage:

8246087698 5703821169127

• = This article is produced by order, with an expected delivery time of 3-4 weeks.

P20

LED 2210lm 116 lm/W 3000K Ra>80 SDCM: 2

Direct

59°

RG 1

UGR<16

L90/B10>100,000

Satin Matt Reflector

Recessed, Indoor

19W 220-240V B10: 21, B16: 34, C10: 35, C16: 58

Light technic
Type of light source:
Luminous flux:
Efficacy:
Colour temperature:
Colour rendering (CRI):
MacAdams factor:
Lifetime:

Colour rendering (CRI):	
MacAdams factor:	
Lifetime:	
Light distribution:	
Optic:	
Beam angle:	
UGR:	
Photobiological safety:	

Control/Dimming

Type:

Туре:	Trailing edge dimming
Protection	
Luminaire class:	Class II
IP Class:	IP20

Energy and approvals Contains light source of energy class:

Contains light source of energy class: Breeam:	D Fulfils Hea 01 for flicker free lighting
Materials and finish	
Housing:	Flame retardant polycarbonate
Colour:	White
Optics:	Aluminium

Mounting/Connection

Mounting:	

Dimensions	
Height (mm) H:	147
Diameter (mm) D:	173
Cut-out (mm):	150
Distance to flammable materials:	50mm
Weight (kg) gross/net:	2 / 1.8
Packaging	

i ucituging	
Packing dimensions (mm):	185 x 185 x 130









