

Rax Eco 180-190



Rax Eco 180-190 White 3000/4000K Ra>80 Trailing edge dimming

Article code: 212584
EAN: 7021982125843



Electrical

Wattage: 8W/17W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 30, B16: 47, C10: 50, C16: 80

Light technic

Type of light source: LED
Luminous flux: 890lm/930lm/1850lm/1950lm
Efficacy: 111/116/109/115lm/W
Colour temperature: 3000/4000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>50,000
Light distribution: Direct
Optic: Reflector
Beam angle: 89°
Visible flicker (PstLM): 0.04
Stroboscopic flicker (SVM): 0
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II
IP Class: IP20

Energy and approvals

Contains light source of energy class: E

Materials and finish

Housing: Polycarbonat (PC)
Colour: White (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Indoor
Connection: 3 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 93
Diameter (mm) D: 210
Weight (kg) gross/net: 1 / 0.78

Packaging

Packing dimensions (mm): 230 x 222 x 110



7 0 2 1 9 8 2 1 2 5 8 4 3