

Rax ECO 200 White 3000/4000K Ra>80 Trailing edge dimming

Article code: 212569
 EAN: 7021982125690



Electrical

Wattage: 13W/24W
 Voltage: 220-240V
 Frequency (Hz): 50/60Hz
 Max. luminaires per circuit breaker: B10: 23, B16: 36, C10: 37, C16: 60

Light technic

Type of light source: LED
 Luminous flux: 1400lm/1490lm/2310lm/2460lm
 Efficacy: 108/115/96/103lm/W
 Colour temperature: 3000/4000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B20>50,000
 Light distribution: Direct
 Optic: Reflector
 Beam angle: 95°
 UGR: UGR<22
 Visible flicker (PstLM): 0.04
 Stroboscopic flicker (SVM):
 Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II

Energy and approvals

Contains light source of energy class: E
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Polycarbonat (PC)
 Colour: White (RAL 9003)
 Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Indoor
 Connection: 3 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 93
 Diameter (mm) D: 216
 Cut-out (mm): 200
 Ceiling void depth (mm): 93
 Weight (kg) gross/net: 1.03 / 0.87

Packaging

Packing dimensions (mm): 240 x 222 x 120

