

System wattage:	30W
Voltage:	220-240V
Frequency (Hz):	50/60Hz
Max. luminaires per circuit breaker:	B10: 32, B16: 50, C10: 52, C16: 85



Type of light source:	LED
Luminous flux:	2970lm
Emergency lumen:	EM 320lm
Efficacy:	99 lm/W
Colour temperature:	3000K
Colour rendering (CRI):	Ra>80
MacAdams factor:	SDCM: 2
Lifetime:	L90/B10>100,000
Light distribution:	Direct
Optic:	Black reflector
Beam angle:	63°
UGR:	UGR<22
Photobiological safety:	RG 1



Type: DALI-2 / Push Dim

Luminaire class:	Class II SELV
IK Class:	IK08
IP Class:	IP44/IP20

Contains light source of energy class:	D
Breem:	Fulfills Hea 01 for flicker free lighting
BVB:	Yes

Housing:	Flame retardant polycarbonate
Colour:	Black
Optics:	Polycarbonat (PC)

Mounting: Recessed, Indoor
Cable: Cable 5x0,75mm²
Connection: 5 pol Linect / screwless terminal block

Height (mm) H:	93
Diameter (mm) D:	216
Cut-out (mm):	200
Ceiling void depth (mm):	90
Weight (kg) gross/net:	1.2 / 1

Packing dimensions (mm): 240 x 240 x 102

