

Sense Driver White 3000lm 26W 700mA DALI / Push Dim

Article code: 820083
 EAN: 7021988200834



Electrical

Wattage: 26W
 System wattage: 26W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 53, C16: 85

Light technic

Lifetime: 100,000

Control/Dimming

Type: DALI / Push Dim
 Driver: 700mA

Protection

Luminaire class: Class II

Energy and approvals

Breem: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Plastic
 Colour: White

Mounting/Connection

Mounting: Recessed, Indoor
 Connection: 5 pol Linect / screwless terminal block

Dimensions


Length (mm) L: 124
 Width (mm) W: 79
 Height (mm) H: 22
 Weight (kg) gross/net: 0.262 / 0.218

Packaging

Packing dimensions (mm): 310 x 35 x 100



SENSE 700mA /3000lm DRIVER DALI



Sense Panels & Driver Kits									
	CU	CU/CA	BA	SENSE 3000lm	SENSE 4000lm	SENSE 5000lm	SENSE 3000lm	SENSE 4000lm	SENSE 5000lm
	(Kv)	(Steps)	(°)	SENSE 413	SENSE 413	SENSE 413	SENSE 413	SENSE 413	SENSE 413
				PHASE DIM	NON DIM	NON DIM	NON DIM	NON DIM	NON DIM
				(700mA)	(700mA)	(1400mA)	(700mA)	(1400mA)	(1400mA)
SENSE ORAL 3-4000lm LED 3000K	80	3	110	2700lm UGR<22	4000lm UGR<22	5000lm UGR<22	2700lm UGR<22	4000lm UGR<22	5000lm UGR<22
SENSE ORAL 3-4000lm LED 4000K	80	3	110	2700lm UGR<22	4000lm UGR<22	5000lm UGR<22	2700lm UGR<22	4000lm UGR<22	5000lm UGR<22
SENSE ORAL 3000lm LED 3000K	80	3	110	2650lm UGR<22	3900lm UGR<22	5000lm UGR<22	2550lm UGR<22	3900lm UGR<22	5000lm UGR<22
SENSE ORAL 3000lm LED 4000K	80	3	110	2750lm UGR<22	4000lm UGR<22	5000lm UGR<22	2750lm UGR<22	4000lm UGR<22	5000lm UGR<22
SENSE PRISM 3-4000lm LED 3000K	80	3	90	2650lm UGR<17	3900lm UGR<19	5000lm UGR<19	2550lm UGR<17	3900lm UGR<19	5000lm UGR<19
SENSE PRISM 3-4000lm LED 4000K	80	3	90	2750lm UGR<17	4000lm UGR<19	5000lm UGR<19	2750lm UGR<17	4000lm UGR<19	5000lm UGR<19
SENSE PRISM 3000lm LED 3000K	80	3	90	2650lm UGR<17	3750lm UGR<17	4800lm UGR<19	2650lm UGR<17	3750lm UGR<17	4800lm UGR<19
SENSE PRISM 3000lm LED 4000K	80	3	90	2750lm UGR<17	3750lm UGR<17	4800lm UGR<19	2750lm UGR<17	3750lm UGR<17	4800lm UGR<19



7 0 2 1 9 8 8 2 0 0 8 3 4