Spike

Spike Graphite Uplight w/ outlet 930lm 3000K Ra>80 Trailing edge dimming

Article code:	623914
EAN:	7021986239140

IP44 IK08



Electrical

Wattage:	10W+6W
System wattage:	16W
Voltage:	220-240V

Light technic

Type of light source:	LED
Socket:	GU10
Light source included:	Yes
Luminous flux:	930lm
Efficacy:	58 lm/W
Colour temperature:	3000K
Colour rendering (CRI):	Ra>80
MacAdams factor:	SDCM: 3
Lifetime:	L70/B50>50,000
Light distribution:	Direct
Optic:	Plastic opal/transparent
Beam angle:	95° down / 15° up

Control/Dimming

Type:	Trailing edge dimming

Protection

Luminaire class:	Class I
IK Class:	IK08
IP Class:	IP44

Energy and approvals

Contains light source of energy class:	E
Breeam:	Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing:	Aluminium
Colour:	Graphite
Optics:	UV-stabilized polycarbonate/ UV-stabilized PMMA

Mounting/Connection

Mounting:	Surface, Outdoor
Connection:	Screwless terminal block

Dimensions

Length (mm) L:	180
Width (mm) W:	171
Height (mm) H:	173
Depth (D):	155
Weight (kg) gross/net:	2.028 / 1.742

Packaging

Packing dimensions (mm):	180 x 165 x 185



7 0 2 1 9 8 6 2 3 9 1 4 0