

StripLine 5m Tunable White 1650lm/m (@6500K) 2700-6500K Ra>90

Article code: 391422
EAN: 7021983914224



Function

Function: Must be combined with 24V driver and LEDDim Smart Color Controller

Electrical

Wattage: 15W/m
System wattage: 15W
Voltage: 24V

Light technic

Type of light source: LED
Luminous flux: 1650lm/m (@6500K)
Efficacy: 110 lm/W
Colour temperature: 2700-6500K
Colour rendering (CRI): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L80/B10>50,000
Light distribution: Direct
Beam angle: 120°
Visible flicker (PstLM): 0.03
Stroboscopic flicker (SVM): 0.04
Photobiological safety: RG 1

Protection

Luminaire class: Class III
IP Class: IP54

Energy and approvals

Energy efficiency class: F

Materials and finish

Optics: Polyuretan (PU)

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
Module: 5m
Cable: Kabel 5m

Dimensions

Length (mm) L: 5000
Width (mm) W: 12
Height (mm) H: 3.2
Weight (kg) gross/net: 0.56 / 0.465

Packaging

Packing dimensions (mm): 190 x 185 x 45

