

Tysnes 66 1500 Grey 5700lm 4000K Ra>80 On/Off

Article code: 120032
 EAN: 7021981200329



Electrical

System wattage: 40W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 14, B16: 23, C10: 22, C16: 36
 Leakage current (mA): 0.31

Light technic

Type of light source: LED
 Luminous flux: 5700lm
 Efficacy: 143 lm/W
 Colour temperature: 4000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B20>100,000
 Lifetime: L90>50,000
 Minimum ambient temperature: -20°C
 Light distribution: Direct
 Optic: Opal
 Beam angle: 117°
 UGR: UGR<25
 Visible flicker (PstLM): 0.01
 Stroboscopic flicker (SVM): 0.05
 Photobiological safety: RG 0

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
 Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: UV-stabilized polycarbonate
 Colour: Grey
 Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor
 Module: 1500
 Connection: 3-pole screwless terminal block with 3x2,5mm² through wiring

Dimensions

Length (mm) L: 1500
 Width (mm) W: 85
 Height (mm) H: 80
 Weight (kg) gross/net: 1.95 / 1.75

Packaging

Packing dimensions (mm): 1525 x 85 x 90

