

Tysnes 66 1500 Grey 5700lm 4000K Ra>80 Sensor

Article code: 120036
EAN: 7021981200367



Electrical

System wattage: 40W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 14, B16: 23, C10: 22, C16: 36
Leakage current (mA): 0.31

Light technic

Type of light source: LED
Luminous flux: 5700lm
Efficacy: 143 lm/W
Colour temperature: 4000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Minimum ambient temperature: -20°C
Light distribution: Direct
Optic: Opal
Beam angle: 117°

Control/Dimming

Type: Sensor

Protection

Luminaire class: Class I
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C

Materials and finish

Housing: UV-stabilized polycarbonate
Colour: Grey
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Indoor
Module: 1500
Connection: 5-pole screwless terminal block with 3x2,5mm² and 2x1,5mm² through wiring

Dimensions

Length (mm) L: 1500
Width (mm) W: 85
Height (mm) H: 80
Weight (kg) gross/net: 2.05 / 1.85

Packaging

Packing dimensions (mm): 1525 x 85 x 90



7 0 2 1 9 8 1 2 0 0 3 6 7