

## Tysnes 66 1500 Grey 5700lm 4000K Ra>80 Sensor

Article code: 120036  
 EAN: 7021981200367



### Electrical

System wattage: 40W  
 Voltage: 220-240V  
 Max. luminaires per circuit breaker: B10: 14, B16: 23, C10: 22, C16: 36  
 Leakage current (mA): 0.31

### Light technic

Type of light source: LED  
 Luminous flux: 5700lm  
 Efficacy: 143 lm/W  
 Colour temperature: 4000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L80/B20>100,000  
 Lifetime: L90>50,000  
 Minimum ambient temperature: -20°C  
 Light distribution: Direct  
 Optic: Opal  
 Beam angle: 117°

### Control/Dimming

Type: Sensor

### Protection

Luminaire class: Class I  
 Fire protection class: 850°C - 30s

### Energy and approvals

Contains light source of energy class: C

### Materials and finish

Housing: UV-stabilized polycarbonate  
 Colour: Grey  
 Optics: UV-stabilized polycarbonate

### Mounting/Connection

Mounting: Surface, Indoor  
 Module: 1500  
 Connection: 5-pole screwless terminal block with 3x2,5mm<sup>2</sup> and 2x1,5mm<sup>2</sup> through wiring

### Dimensions

Length (mm) L: 1500  
 Width (mm) W: 85  
 Height (mm) H: 80  
 Weight (kg) gross/net: 2.05 / 1.85

### Packaging

Packing dimensions (mm): 1525 x 85 x 90

