

Tysnes 66 1200 Grey 5040lm 4000K Ra>80 DALI

Article code: 120039
EAN: 7021981200398



Electrical

System wattage: 34W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 14, B16: 24, C10: 25, C16: 40
Leakage current (mA): 0.29

Light technic

Type of light source: LED
Light source included: Yes
Luminous flux: 5040lm
Efficacy: 148 lm/W
Colour temperature: 4000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct
Optic: Opal
Beam angle: 116°

Control/Dimming

Type: DALI

Protection

Luminaire class: Class I
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C

Materials and finish

Housing: UV-stabilized polycarbonate
Colour: Grey
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Indoor
Module: 1200
Connection: 5-pole screwless terminal block with 5x2,5mm2 through wiring

Dimensions

Length (mm) L: 1200
Width (mm) W: 85
Height (mm) H: 80
Weight (kg) gross/net: 1.68 / 1.53

Packaging

Packing dimensions (mm): 1225 x 85 x 90



7 0 2 1 9 8 1 2 0 0 3 9 8