

## UniLED IsoSafe White 670lm 2700K Ra 98 Trailing edge dimming

Article code: 904201  
 EAN: 7021989042013  
 Replaces: 912290



### Electrical

Wattage: 7W  
 System wattage: 8.5W  
 Voltage: 220-240V  
 Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

### Light technic

Type of light source: LED  
 Luminous flux: 670lm  
 Efficacy: 79 lm/W  
 Colour temperature: 2700K  
 Colour rendering (CRI): Ra 98  
 MacAdams factor: SDCM: 2  
 Lifetime: L90/B10 > 100,000  
 Light distribution: Direct  
 Optic: Reflector  
 Beam angle: 42°  
 UGR: UGR < 22

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class II SELV

### Energy and approvals

Contains light source of energy class: F  
 Breeam: Fulfil Hea 01 for flicker free lighting  
 BVB: Yes

### Materials and finish

Housing: Aluminium  
 Colour: Matte white (RAL 9003)  
 Optics: Tempered glass

### Mounting/Connection




Mounting: Recessed, Indoor / Outdoor  
 Connection: Screwless terminal block

### Dimensions

Height (mm) H: 37  
 Diameter (mm) D: 94  
 Cut-out (mm): 76  
 Ceiling void depth (mm): 35  
 Distance to flammable materials: 0mm  
 Weight (kg) gross/net: 0.48 / 0.4

### Packaging

Packing dimensions (mm): 115 x 100 x 95



7 021989042013