

Electrical System wattage:

Voltage:

Wax Black 13° 3200lm 3000K Ra>80 On/Off

Article code: EAN:

Max. luminaires per circuit breaker:

8246091558 5703821173261

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Class II

Е

Die-cast aluminium Black (20% gloss)

Cable 2x1mm² 10m

0,0403m² - Max 5,3 kg

Pole, wall, bollard or earthing rod, Outdoor

Tempered glass

48W 220-240V B10: 32, B16: 50, C10: 52, C16: 85

Light technic	
Type of light source:	LED
Luminous flux:	3200lm
Efficacy:	67 lm/W
Colour temperature:	3000K
Colour rendering (CRI):	Ra>80
MacAdams factor:	SDCM: 2
Lifetime:	L90/B10>100,000
Light distribution:	Direct
Optic:	Reflector spot 13dg.
Beam angle:	13°
Control/Dimming	
Туре:	On/Off
Protection	

Luminaire class:

Energy and approvals

Contains light source of energy class:	E
Breeam:	Fulfils Hea 01 for flicker free lighting
BVB:	Yes

Materials and finish

Housing: Colour: Optics:

Mounting/Connection

Mounting: Cable: Wind projected area:

Dimensions

Packaging	
Weight (kg) gross/net: 4.	7 / 4.5
Diameter (mm) D:	180
Height (mm) H:	268

rackaging	
Packing dimensions (mm):	275 x 275 x 275



R





