

Sense Opalprism TW 300x1200



The Sense panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency. Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Troldekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available in Tunable White 2700-6500K LEDDim or DALI Type 8 depending on whichever driver kit is selected (accessory).

Sense Opalprism TW 300x1200




Produkt- och miljöbilder



Artikel	Skydd	Styrutrustning	Montering/anslutning	Mått
 7018057 Sense TW 300x1200 Vit Opalprismatisk 4000lm 2700-6500K Ra>80 LED SDCM:3 L80/B20>50.000 Beam: 84°, Direkt, Opalprismatisk	Klass III IP40 IK10		Infälld, Indoor Quick connector	L1197 x W297 x H44
Driver				
 7982168 Sense TW Driver Vit 4000lm 38W TW DALI Type 8 38W	Klass II	TW DALI Type 8	Indoor 5 pol Linect / skruvlös kopplingsplint	L215 x W70 x H32
 7981849 Sense TW Vit 4000lm 40W TW LEDDim 40W	Klass II IP20	TW LEDDim	Indoor 3 pol Linect / skruvlös kopplingsplint	
Tillbehör				
 7024866 Sense 300x1200 Vit Utanpåliggande enhet				L1203 x W303 x H47
 7015943 300x1200 Vit Gipstak/Troldtekt Infälld ram				L325 x W1225 x H55
 7345892 Nödljusbox Driver DALI / EM Självtest, DALI nödbelysning 3 h				L270 x W75 x H35
 7014358 Sense 2m Wireset				L2000
 7014366 Sense 600x600 Asymmetrisk Beslag				L44 x W5 x H2.5
 7344588 Nödljusbox On-Off/Bakkantsdim / EM Självtest, Nödbelysning 3 timmar				L270 x W75 x H35



Artikel	Skydd	Styrutrustning	Montering/anslutning	Mått
 7345302 Nödljusbox Driver DALI / EM DALI/Självttest, Nödbelysning 3 timmar				L270 x W75 x H35