

Hurdal Connect



Hurdal Connect is a compact and stylish ceiling and wall luminaire featuring an integrated SG Connect sensor for smart and energy-efficient lighting control. The sensor switches the light on when motion is detected and off after a defined time period, delivering significant energy savings. A built-in daylight sensor can be activated to maintain the desired light level at all times. Configuration is simple via the SG Connect Commissioning App, and the luminaire can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Hurdal Connect combines high performance with easy installation. It mounts directly on ceilings or walls, with cable entry at both ends and in the middle, and through-wiring ensures quick and efficient connection. The luminaire is IP44-rated and features a robust steel housing with aluminum end caps for long-lasting and reliable operation.

Hurdal Connect



Produkt- och miljöbilder





Artikel		Skydd	Styrutrustning	Montering/anslutning	Mått
	7027820	Klass I	Connect	Utanpåliggande, Indoor	L600 x W72 x H76
	Hurdal Connect 600 Vit 1590lm	IP44		3-polig skruvlös kopplingsplint med	
	3000K Ra>80 Connect			3x2,5 mm ² genomgående ledningar	
	12W LED				
	133 lm/W SDCM:3				
	L80/B20>100.000, L90>50.000				
	Direkt, Opal				
	7027821	Klass I	Connect	Utanpåliggande, Indoor	L1200 x W72 x H76
	Hurdal Connect 1200 Vit 3460lm	IP44		3-polig skruvlös kopplingsplint med	
	3000K Ra>80 Connect			3x2,5 mm ² genomgående ledningar	
	24W LED				
	144 lm/W SDCM:3				
	L80/B20>100.000, L90>50.000				
	Direkt, Opal				
	7027822	Klass I	Connect	Utanpåliggande, Indoor	L1500 x W72 x H76
	Hurdal Connect 1500 Vit 4640lm	IP44		3-polig skruvlös kopplingsplint med	
	3000K Ra>80 Connect			3x2,5 mm ² genomgående ledningar	
	31W LED				
	150 lm/W SDCM:3				
	L80/B20>100.000, L90>50.000				
	Direkt, Opal				