




Design: Christian Hvidt. Mast top-mounted LED luminaire. IP66. LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Base and diffuser in textured light grey. Direct lens optical solutions (Multilens). Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with six-metre connection cable. Prepared for mounting on 60 mm mast. Safety class II.










Product- and environment images



Article		Protection	Control gear	Mounting/Connection	Dimensions
3000K					
	8246087892 High5 Grey Lens 1 2560lm 3000K Ra>70 On/Off 23W LED 111 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087915 High5 Lens 2 2780lm 3000K Ra>70 On/Off 23W LED 121 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246094102 High5 Grey Lens 2 2780lm 3000K Ra>70 On/Off 23W LED 121 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2, Glass Clear	Class II IP66 IK08	On/Off	Pole - Side (Ø60/48mm), Outdoor Cable 2x1mm ² 6m	L550 x W175 x H90
	8246087876 • High5 Grey Lens 1 1150lm 3000K Ra>70 On/Off 10W LED 115 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087889 • High5 Grey Lens 1 2080lm 3000K Ra>70 On/Off 18W LED 116 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087902 • High5 Grey Lens 2 2260lm 3000K Ra>70 On/Off 18W LED 126 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200

Article		Protection	Control gear	Mounting/Connection	Dimensions
	8246092010 • High5 Grey Lens 1 1150lm 3000K Ra>70 Lumistep LS8 10W LED 115 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	Lumistep LS8	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
4000K					
	8246087863 High5 Grey Lens 1 2730lm 4000K Ra>70 On/Off 23W LED 119 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087931 High5 Grey Lens 2 2960lm 4000K Ra>70 On/Off 23W LED 129 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2,	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087070 • High5 Grey Lens 1 2210lm 4000K Ra>70 On/Off 18W LED 123 lm/W SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087850 • High5 Grey Lens 1 4000K Ra>70 On/Off 10W LED SDCM:3 L80/B10>80,000 Lens 1, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200
	8246087928 • High5 Grey Lens 2 2410lm 4000K Ra>70 On/Off 18W LED 134 lm/W SDCM:3 L90/B10>100,000, L98/B50>50,000 Lens 2, Lens	Class II IP66 IK08	On/Off	Post - top (Ø60mm), Outdoor Cable 2x1mm ² 6m	L430 x W175 x H200

Accessories

Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249042083 • Galvanized Pole 3m Steel				
 8249042096 • Galvanized Pole 4m Steel				
 8249042106 • Galvanized Conical Pole 3m Steel				
 8249042119 • Galvanized Conical Pole 4m Steel				
 8249042180 • Galvanized Ground anchor Steel				
 8249042203 • Mounting unit				
 8249043862 • Grey Design pole 3m Steel				
 8249043891 • Grey Design pole 4m Steel				
 8249043943 • Galvanized Reducer part from Ø76 to Ø60 Steel				L230 x W98 x H230

• = This article is produced by order, with an expected delivery time of 3-4 weeks.