

# **CE – Declaration of Conformity**

Document: Product Inspection: Risk Assessment: CE-UKCA221212A\_Sense IP65 PI221205B RA210811A

We,

#### SG Armaturen AS Skytterheia 25 N-4790 Lillesand - Norway

declare under sole responsibility that the product

## Luminaire

Туре

# Sense IP65

Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

Directive 2014 / 30 / EU	Directive 2014 / 35 / EU	Directive 2009 / 125 / EF	
		(Regs 244/2009, 245/2009, 347/2010)*	
Electromagnetic compatibility (EMC)	Low Voltage directive (LVD)	Ecodesign requirements (ECO) * As applicable and including amendments	

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires for emergency lighting)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)

CE declaration date: 2022

Statement of Conformity

Manufacturer Lillesand, 12/12-2022 Place and date of issue Martin Ettrup Approval Engineer Name of authorized person issued by SG Armaturen AS

Signature of authorized person



# **UKCA – Declaration of Conformity**

Document: Product Inspection: Risk Assessment: CE-UKCA221212A\_Sense IP65 PI221205B RA210811A

We,

SG Armaturen AS Skytterheia 25 N-4790 Lillesand - Norway

declare under sole responsibility that the product

### Luminaire

Туре

### Sense IP65

Name(s)

#### To which this declaration relates is in conformity with the following UK-regulations:

UK SI 2016 No. 1091	UK SI 2016 No. 1101	UK SI 2010 No. 2617	UK SI 2012 No. 3032
The Electromagnetic	The Electrical	The Ecodesign for Energy-Related	The Restriction of the Use of Certain
Compatibility	Equipment (Safety)	Products Regulations 2010	Hazardous Substances in Electrical
Regulations 2010	Regulations 2016	Equipment (Safety) Regulations 2016	Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-2:2012	(Luminaires - Recessed)
EN 60598-2-22:2022	(Luminaires for emergency lighting)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)
UK SI 2021 No. 1095	(Luminaires – The Ecodesign for Energy-Related products and Energy Information)

UKCA declaration date: 2022

Statement of Conformity

Manufacturer

Lillesand, 12/12-2022 Place and date of issue Martin Ettrup Approval Engineer Name of authorized person issued by SG Armaturen AS

Signature of authorized person



Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
5703821181655 5703821181662 5703821181426 5703821181204 5703821181617 5703821181624 5703821181631 5703821181631 5703821181440 57038211814433 5703821181433	Sense IP65 595x595 White Sense IP65 599x599 White Sense IP65 595x595 White Sense IP65 595x595 White Sense IP65 595x595 White Sense IP65 599x599 White Sense IP65 599x599 White Sense IP65 595x595 White Sense IP65 599x599 White Sense IP65 599x599 White Sense IP65 599x599 White Sense IP65 595x595 White	5060lm 4000K Ra>80 DALI Emergency 3H 5060lm 4000K Ra>80 DALI Emergency 3H 5110lm 4000K Ra>90 DALI Emergency 3H 5110lm 4000K Ra>90 DALI / Push Dim 5060lm 4000K Ra>80 DALI / Push Dim 5050lm 4000K Ra>80 DALI / Push Dim 4670lm 3000K Ra>90 DALI Emergency 3H 5110lm 4000K Ra>90 DALI Emergency 3H 4830lm 3000K Ra>90 DALI / Push Dim 5110lm 4000K Ra>90 DALI / Push Dim 4670lm 3000K Ra>90 DALI / Push Dim	130253 130253 130253 130253 130253 130253 130253 130253 130253 130253 130253 130253
5703821181648	Sense IP65 595x595 White	4830lm 3000K Ra>80 DALI Emergency 3H	130253

