

CE – Declaration of Conformity

Document: CE-UKCA231123A Nano

Product Inspection: PI230116A

DEKRA report: 4900288.50, 4900289.50

Risk Assessment: RA230113A

We, SG Armaturen AS

Skytterheia 25

N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire
Туре
Nano
Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

Directive 2014 / 30 / EU	Directive 2014 / 35 / EU	Directive 2009 / 125 / EF
		(Regs 244/2009, 245/2009, 347/2010)*
Electromagnetic compatibility (EMC)	Low Voltage directive (LVD)	Ecodesign requirements (ECO) *As applicable and including amendments

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022 (Luminaires - General requirements)

EN 60598-2-2:2012 (Luminaires - Recessed)

EN 62471:2008 (Luminaires – Photobiological safety of lamps and lamp systems)

EN 62493:2015 (EMF – Lighting equipment related to human exposure)

EN 55015:2019+A11:2020 (EMC - Radio disturbance)

EN 61000-3-2:2019 (EMC - Harmonics)

EN 61000-3-3:2013+A1:2019 (EMC – Voltage change, fluctuation & flicker)

EN 61547:2009 (EMC - Immunity)

CE declaration date: 2023

Statement of Conformity issued by SG Armaturen AS

ManufacturerMartin EttrupLillesand, 23/11-2023Approval EngineerPlace and date of issueName of authorized person

Signature of authorized persor



UKCA – Declaration of Conformity

Document: CE-UKCA231123A_Nano

Product Inspection: PI230116A

DEKRA report: 4900288.50, 4900289.50

Risk Assessment: RA230113A

We, SG Armaturen AS

Skytterheia 25

N-4790 Lillesand - Norway

declare under sole responsibility that the product

	Luminaire	
	Туре	
	Nano	
_	Name(s)	

To which this declaration relates is in conformity with the following UK-regulations:

UK SI 2016 No. 1091	UK SI 2016 No. 1101	UK SI 2010 No. 2617	UK SI 2012 No. 3032
The Electromagnetic Compatibility Regulations 2010	The Electrical Equipment (Safety) Regulations 2016	The Ecodesign for Energy-Related Products Regulations 2010 Equipment (Safety) Regulations 2016	The Restriction of the Use of Certain Hazardous Substances in Electrical Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022 (Luminaires - General requirements)

EN 60598-2-2:2012 (Luminaires - Recessed)

EN 62471:2008 (Luminaires – Photobiological safety of lamps and lamp systems)

EN 62493:2015 (EMF – Lighting equipment related to human exposure)

EN 55015:2019+A11:2020 (EMC - Radio disturbance)

EN 61000-3-2:2019 (EMC - Harmonics)

EN 61000-3-3:2013+A1:2019 (EMC – Voltage change, fluctuation & flicker)

EN 61547:2009 (EMC - Immunity)

UK SI 2021 No. 1095 (Luminaires – The Ecodesign for Energy-Related products

and Energy Information)

UKCA declaration date: 2023

Statement of Conformity issued by SG Armaturen AS

ManufacturerMartin EttrupLillesand, 23/11-2023Approval EngineerPlace and date of issueName of authorized person

Signature of authorized person



Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
7021989070030	Nano White 80lm	2700K Ra>90	702050
7021989070023	Nano White 90lm	3000K Ra>90	702050
7021989070054	Nano White 90lm	4000K Ra>90	702050
7021989070047	Nano White 90lm	3000K Ra>90	702050
7021989070016	Nano White 80lm	2700K Ra>90	702050
7021989070061	Nano Black 80lm	2700K Ra>90	702050
7021989070078	Nano Black 90lm	3000K Ra>90	702050
7021989070177	Nano Tilt White 240lm	3000K Ra>90	702050
7021989070184	Nano Tilt White 270lm	4000K Ra>90	702050
7021989070191	Nano Tilt Black 240lm	2700K Ra>90	702050
7021989070207	Nano Tilt Black 240lm	3000K Ra>90	702050
7021989070160	Nano Tilt White 240lm	2700K Ra>90	702050
Drivers			

7021988200919	Nano White Driver 17W 350mA Trailing edge dimming / Push Dim
7021988200728	Nano White Driver 9W 350mA 1-10V / Push Dim
7021988200780	Nano White Driver 4,2W 350mA Trailing edge dimming